


Section 1. Product and Company Identification

Manufacturer	: Seacoat SCT, LLC 31902 Industrial Park Dr., Pinehurst, Texas, USA. 77362 USA Tel: +1-832-237-4400; Fax: +1-832-237-4414
Emergency Telephone	: +1-832-237-4400; +1-713-261-0558. For Chemical Emergency Only (spill, leak, fire, exposure, or accident)
Material Name	: Sea-Speed V10X Ultra – Clear (Part A) Activator
MSDS No.	: 042017ASSV10CLR-A
CAS No.	: N/A - Mixture

This Material Safety Data Sheet conforms to ANSI Z400.5, and to the format requirements of the International Chemical Safety Cards (ICSCs) of the Global Harmonizing System (GHS). THIS MSDS COMPLIES WITH 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD).
IMPORTANT: Read this MSDS before handling and disposing of this product. Pass this information on to employees, customers and end users of this product.

Section 2. Hazards Identification

Emergency overview:

Form	: Liquid
Color	: Clear to slightly yellow
Odor	: Amine like
Symbols	: 
Statements	: May cause eye tissue damage Harmful or fatal if Swallowed

Potential Health effects:

Eye Contact	: Irritating. May cause eye tissue damage if not removed quickly
Skin Contact	: Moderately irritating
Inhalation	: May cause respiratory tract irritation
Ingestion	: May cause irritation to mouth, throat and stomach

Section 3. Composition Information

HAZARDOUS Ingredients:

Dibutyltin Dineodecanoate	: CAS No.251168-22-3	< 5%
3-Aminopropyltriethoxy silane	: CAS No.919-30-2	< 10%

Section 4. First Aid Measures

Skin Contact	: Wash with soap and water for at least 10 minutes. Remove contaminated clothing and wash thoroughly before re-use. Consult a doctor if skin irritation persists.
Inhalation	: If breathing difficulty occurs remove affected person out into fresh air. Consult a physician if nose, throat or eye irritation persists.
Eye Contact	: Rinse eyes thoroughly with fresh water for ten minutes. Use eye rinse solution. If irritation persists, contact an ophthalmologist.

Section 4. First Aid Measures (Continued)

Ingestion	: Rinse mouth thoroughly with water. Do not induce Vomiting. Give plenty of fluids (water). If discomfort persists, contact a physician.
Notes to Physician	: If substance is ingested in large amounts, apply therapy for chemical burn. Early endoscopy in order to assess mucosa lesions in the esophagus and stomach. If needed, aspirate left over substance.

Section 5. Fire Fighting Measures

Flash point	: > 100°C (TCC)
Auto ignition temperature	: Not determined
Lower Explosive limit %	: Not determined
Upper Explosive Limit %	: Not determined
Suitable extinguishing media	: Foam, CO2, dry powder. Reacts with water and hydrolysis is exothermic.
Specific hazards during firefighting	: NOx from fire and fumes
Special protective equipment For fire fighters	: As in any fire, self contained positive pressure breathing apparatus, (MSHA,NIOSH) or approved equivalent and full protective gear.

Section 6. Accidental Release Measures

Personal	: Ensure proper ventilation. Avoid contact with skin and eyes.
Environmental	: Follow local, state, federal and or provincial laws and regulations. Do not contaminate groundwater, soil streams, ponds or lakes.
Methods for cleanup	: Use absorbent materials such as universal binder, saw dust, sand or other appropriate material. Place in marked container and sealed container for disposal in accordance with existing regulations.

Section 7. Handling and Storage

Handling	: Use in well ventilated areas. Avoid direct skin and eye contact. Avoid breathing fumes or mist. Wash hands with soap and water after handling.
Storage	: store between 5°C - 38°C

Section 8. Exposure Controls / Personal Protection

Engineering controls	: Provide good ventilation in confined areas.
Eye & face protection	: Wear safety glasses with side shields.
Hand protection	: Butyl rubber. Wear protective gear as needed.
Respiratory protection	: Wear a NIOSH/MSHA approved respirator during application whenever workplace conditions warrant respirator use.
Hygiene measures	: Avoid contact with skin, eyes and or clothing. Do not inhale vapors or mist. Do not eat, drink or smoke while using this product. Remove contaminated clothing and thoroughly wash before re-use.

Section 9. Physical and Chemical Properties

Appearance:

Form	: Liquid
Color	: Colorless to yellow
Odor	: Pungent

Safety Data:

PH	: Not determined
Flash point	: > 100°C
Melting point	: Not determined
Boiling Point	: Not determined
Evaporation rate	: <1 (n-Butyl Acetate=1)
Flammability limits in air	: Not determined
Auto ignition temperature	: > 300°C
Vapor density	: >1 Air =1
VOC mixed A & B	: 21.8 gr/Liter incl water and exempt compounds

Section 10. Stability and Reactivity

Hazardous decomposition products	: Ethanol in case of hydrolysis.
Hazard reactions	: No dangerous reactions known.
Additional information	: Incompatibility with humidity, water, alkalis, acids.

Section 11. Toxicological Information

Sensitization	: Possibility of skin sensitization may occur under prolonged exposure.
Carcinogenicity	: None.
Genotoxicity	: Not mutagenic.
Toxicity to reproduction	: No evidence of effects of reproductive/developmental toxicity.
Notes	: Prolonged exposure to spray mists can cause dizziness, nausea, headaches and be irritating to the eyes, respiratory tract and skin. Ingestion may cause gastrointestinal irritation or damage.

Section 12. Ecological Information

The data we have available at our disposal does not necessitate identification as an environmentally hazardous substance. An environmental hazard may be considered due to unprofessional handling and or disposal.

Bioaccumulation	: Not bioaccumulative
------------------------	-----------------------

Section 13. Disposal Considerations

Disposal method	: PART A in its individual state may be a hazardous waste when discarded or disposed of according to Federal regulations (40CFR 261.4 (b) (4). Under RCRA, it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Do not allow this material into sewers and water supplies. Waste must be disposed of in accordance with Federal, state and local regulations.
Advice on disposal	: Mix all residual part A with Part B and allow it to cure fully in an open container. Cured product may be disposed of as a non-hazardous solid waste.

Section 14. Transport Information

Department of Transportation (DOT):

UN 3267	: CORROSIVE LIQUID BASIC, ORGANIC, N.O.S. (3-aminopropyl-triethoxysilane)
Transport hazard Class	: 8
Packing group	: II
Environmental Hazard	: --

Air Transport (ICAO-TI/IATA –DGR):

UN 3267	: CORROSIVE LIQUID BASIC,ORGANIC, N.O.S. (3-aminopropyltriethoxysilane)
Transport hazard class	: 8
Packing Group	: II
Environmental hazard	: --
Special precautions for use	: Yes
IATA-Cargo plane	: EGR Code 8L
IATA-Passenger plane	: EGR Code 8L

SEA TRANSPORT (IMDG):

UN 3267	: CORROSIVE LIQUID BASIC ORGANIC N.O.S. (3-aminopropyltriethoxysilane)
Transport hazard class	: 8
Packing Group	: II
Environmental hazard (Marine Pollutant)	: --
Special precautions for use	: Yes
EmS	: F-A, S-B

Note: Clear of living quarters; Keep separate from acids.

Section 15. Regulatory Information

OSHA Clean air act (112)	: None listed
CERCLA reportable quantities	: None listed
SARA TITLE III (311/312)	
Fire	: No
Pressure	: No
Reactivity	: No
Acute	: No
Chronic	: No
SARA TITLE III (313)	: Xylene (mixed Isomers), standard reporting threshold.
TSCA	: None listed
California Proposition 65	: None listed
International Chemical Inventory	
USA (TSCA)	: Yes
Canada (DSL)	: Yes
Australia (AICS)	: Yes
New Zealand (NZIoC)	: Yes
Europe (EINECS)	: Yes
Japan (MITI)	: Yes
South Korea (TCCL)	: Yes
China	: Yes

Section 16. Other Information

Key to abbreviations:

CAS	: Chemical Abstracts Service
CERCLA	: Comprehensive Environmental Response, Compensation, and Liability Act
IATA-DGR	: The International Air Transport Association - Dangerous Goods Regulations
ICAO-TI	: International Civil Aviation Organisation – Technical Instructions
IMDG	: The International Maritime Dangerous Goods
MSDS	: Material Safety Data Sheet
MSHA	: Mine Safety and Health Administration
NIOSH	: National Institute for Occupational Safety and Health
NOx	: Nitrogen Oxide
OSHA	: Occupational Safety and Health Administration
RCRA	: Resource Conservation and Recovery Act
SARA	: Superfund Amendments and Reauthorization Act
TCC	: Tag Closed Cup
TSCA	: Toxic Substances Control Act
VOC	: Volatile Organic Compound

Manufacturer disclaimer

This information and any recommendations, technical or otherwise, are presented in good faith and believed to be correct as of the date prepared. Recipients of this information and recommendations must make their own determination as to its suitability for their purposes. In no event shall Seacoat SCT, LLC assume liability for damages or losses of any kind or nature that result from the use of or reliance upon this information and recommendations. SEACOAT SCT,LLC EXPRESSLY DISCLAIMS ANY REPRESENTATIONS AND WARRANTIES OF ANY KIND, WHETHER EXPRESS OR IMPLIED, AS TO THE ACCURACY, COMPLETENESS, NON-INFRINGEMENT, MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR PURPOSE (EVEN IF SEACOAT SCT,LLC IS AWARE OF SUCH PURPOSE) WITH RESPECT TO ANY INFORMATION AND RECOMMENDATIONS PROVIDED. Reference to any trade names used by other companies is neither a recommendation nor an endorsement of the corresponding product and does not imply that similar products could not be used. Seacoat SCT, LLC reserves the right to make any changes to the information and/or recommendations at any time, without prior or subsequent notice.

~~ We have your bottom covered ~~